

According to IEC 60947-3, EN 60947-3, VDE 0660 part 107



Rated Thermal Current $I_U/I_{th}/I_{the}$					A	40
Rated Insulation Voltage U_i ¹					V	690
Rated Impulse Withstand Voltage U_{imp}					kV	6
Rated Operational Current I_e						
AC-21A	Switching of resistive loads, including moderate overloads			A	40	
AC-22A	Switching of combined resistive or low inductive loads including moderate overloads		220 V–500 V	A	40	
			660 V–690 V		40	
Rated Utilization Category						
AC-3	Direct-on-line starting	3 phase, 3 pole	220 V–240 V	kW	7,5	
			380 V–440 V		11	
			500 V		15	
			660 V–690 V		11	
AC-23A	Frequent switching of motors or other high inductive loads	3 phase, 3 pole	220 V–240 V	kW	7,5	
			380 V–440 V		15	
			500 V		18,5	
			660 V–690 V		15	
Short Circuit Protection						
Max. fuse size		gG-characteristic			A	50
Rated short-time withstand current		(1 s-current)			A	500
For connections with insulated ring and fork type cable terminal - copper wires only						
Single-core or stranded wire					mm ²	16
Flexible wire					mm ²	10
Flexible wire with sleeving in accordance with DIN 46228					mm ²	10

¹ Valid for lines with grounded common neutral termination, overvoltage category III, Other values on request.

Miscellaneous

Tightening torque of terminal screw:	1,8 Nm (16 lb-in)	
Minimum Voltage:	on request	
Power loss per contact at I_U :	1 W	
Resistance to vibration:	min. 4 g, 2-100 Hz, 1,6 mm	
Resistance to shock:	min. 5 g, 6 ms	
Min. Ambient Temperature of Stages:	-5 °C	
Max. Ambient Temperature of Stages:	open at 100 % I_U/I_{th}	50 °C during 24 hours with peaks up to 55 °C
	enclosed at 100 % I_{the}	35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5 °C no shock load permissible)	

Approvals and Standards

IEC 60947 EN 60947			 GB14048.3			
-----------------------	---	---	---	---	---	---

USA / Canada



Rated Thermal Current $I_U/I_{th}/I_{the}$				A	40
Rated Insulation Voltage U_i				V	600
Rated Operational Current I_e					
Pilot Duty			Heavy	VAC	A600
Ampere Rating	Resistive or low inductive loads	ON/OFF 1-0-2	600 V	A	40
			600 V		40
Max. Permissible Wire Gage - copper wires only					
	Single-core or stranded wire			AWG	6
	Flexible wire: AWG wire (without sleeving)			AWG	6
Ratings					
	Standard motor load, DOL - Rating (similar AC-3)	3 phase 3 pole	110 V – 120 V	HP	5
220 V – 240 V			15		
440 V – 480 V			25		
550 V – 600 V			30		

Miscellaneous

Tightening torque of terminal screw:	1,8 Nm (16 lb-in)	
Minimum Voltage:	on request	
Power loss per contact at I _U :	1 W	
Resistance to vibration:	min. 4 g, 2-100 Hz, 1,6 mm	
Resistance to shock:	min. 5 g, 6 ms	
Min. Ambient Temperature of Stages:	-5 °C	
Max. Ambient Temperature of Stages:	open at 100 % I _U /I _{th}	50 °C during 24 hours with peaks up to 55 °C
	enclosed at 100 % I _{thE}	35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5 °C no shock load permissible)	

Approvals and Standards

IEC 60947 EN 60947	cULus	SA	CCC GB14048.3	Lloyd's Register	EAC	
-----------------------	-------	----	------------------	---------------------	-----	--