


## 1513C Multi-Conductor - Flexible, CM Rated Cable

For more Information  
please call

1-800-Belden1



### Description:

24 AWG stranded (7x32) TC conductor, polyolefin insulation, individually shielded Beldfoil® (100% coverage) numbered/color-coded PVC jackets, jackets and shields bonded to strip simultaneously, overall Beldfoil shield and 24 AWG TC drain wire.

### Physical Characteristics (Overall)

#### Conductor

##### AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
12	24	7x32	TC - Tinned Copper	0.6096

#### Insulation

##### Insulation Material:

Insulation Material	Wall Thickness (mm)	Dia. (mm)
PO - Polyolefin	0.2032	1.016

#### Inner Shield

##### Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

##### Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

#### Inner Jacket

##### Inner Jacket Material:

Inner Jacket Material	Nom Wall (mm)	Nom. Dia. (mm)
PVC - Polyvinyl Chloride	0.3556	2.8194

##### Inner Jacket Color Code Chart:

Number	Color
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Purple
8	Gray
9	White
10	Black
11	Tan
12	Pink

#### Outer Shield

##### Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

## 1513C Multi-Conductor - Flexible, CM Rated Cable

### Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
18	7x26	TC - Tinned Copper

### Outer Jacket

#### Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.143

Outer Jacket Ripcord: Yes

### Overall Cabling

Overall Nominal Diameter: 14.249 mm

### Pair

#### Pair Color Code Chart:

Color
Red & Black

#### Pair Lay Length & Direction:

Lay Length (mm)	Twists/ft. (twist/m)
44.449825	22.475

## Mechanical Characteristics (Overall)

Operating Temperature Range: -35°C To +75°C

Bulk Cable Weight: 191.085 Kg/Km

Max. Recommended Pulling Tension: 980.383 N

Min. Bend Radius (Install)/Minor Axis: 139.700 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

### Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
50

### Nom. Inductance:

Inductance (µH/m)
0.59058

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
101.711

## 1513C Multi-Conductor - Flexible, CM Rated Cable

**Nom. Capacitance Cond. to Other Conductor & Shield:**

Capacitance (pF/m)  
190.298

**Nominal Velocity of Propagation:**

VP (%)  
66

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/km)  
76.4473

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 52.168 Ohm/km

**Max. Operating Voltage - UL:**

Voltage  
300 V RMS

**Max. Recommended Current:**

Current  
1.05 Amps per conductor @ 25°C

### Notes (Overall)

**Notes:** Jacket and shield are bonded so both can be removed with automatic stripping equipment. Beldfoil® provides high reliability with ease of termination.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1513C B591000	305 MT	80.740 KG	BLACK, MATTE	C	12 PR #24 PP FS PVC FS PVC
1513C B59500	152 MT	40.597 KG	BLACK, MATTE	C	12 PR #24 PP FS PVC FS PVC

**Notes:**  
C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 04-18-2008

© 2008 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.