



JUNCTION BOX

2K-12-2,5²/w



2K-12-2,5²/w

Junction box

85 x 85 x 37 mm

Article number: 34411201

Junction box acc. DIN EN 60670 (VDE 0606), 12 entries, 2 floor entries, with self-sealing, soft inlet membranes, tools not required for opening the cable entry, seal range 2 - 14 mm, with internal fixing positions

white, with screw terminal 5-pole - 2.5 mm²



Technical data

Measures

| | |
|---------|-------|
| Width: | 85 mm |
| Length: | 85 mm |
| Height: | 37 mm |

Material

| | |
|--------|------------------------------------|
| Base: | polypropylene, membrane out of TPE |
| Cover: | Polypropylen, Copolymer |

Other attributes

| | |
|------------------------------|---------------------|
| Rated cross section: | 2,5 mm ² |
| Tackable: | No |
| Rated insulation voltage AC: | 400 V |
| Explosion safety: | none |

Accessory

- ZEL 2K-12

- HandyQuick SQ 52

- HandyQuick SQ 32

- HandyClip VC 21

- HandyClip VC 20

- HandyGrip VG 21 w

- HandyGrip VG 20 w

- HandyGrip VG 21

- HandyGrip VG 20

- HandyQuick SQ51

- HandyQuick SQ81

- HandyQuick SQ 31



JUNCTION BOX

2K-12-2,5²/w

| | |
|---------------------|---|
| Fire protection: | none |
| sealable: | No |
| Heavy metals-free: | Yes |
| PVC-free: | Yes |
| Silicone-free: | Yes |
| Ingress protection: | IP55 - acc. EN 60529 / DIN VDE 0470-1 |
| Weatherproof: | No |

Environmental attributes

| | |
|--|--------|
| Ambient temperature (min.): | -25 °C |
| Ambient temperature (max.): | 40 °C |
| Ambient temperature (24 h): | 35 °C |
| Max. rel. humidity at 25° C (short Therm): | 95% |
| Max. rel. humidity at 40° C: | 50% |