



JUNCTION BOX

# 2K-12 AB-2,5<sup>2</sup>/w



## 2K-12 AB-2,5<sup>2</sup>/w

**Junction box**

85 x 85 x 37 mm

Article number: 34511201

Junction box acc. DIN EN 60670 (VDE 0606), 12 entries, 2 floor entries, with self-sealing, soft inlet membranes, tools not required for opening the cable entry, seal range 2 - 14 mm, with external fixing positions

white, with screw terminal 5-pole - 2.5 mm<sup>2</sup>



### Technical data

#### Measures

Width:	85 mm
Length:	85 mm
Height:	37 mm

#### Material

Base:	polypropylene, membrane out of TPE
Cover:	Polypropylen, Copolymer

#### Other attributes

Color:	miscellaneous
Rated cross section:	2,5 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	400 V

### Accessory

- ZEL 2K-12
- HandyQuick SQ 52
- HandyQuick SQ 32
- HandyClip VC 21
- HandyClip VC 20
- HandyGrip VG 21 w
- HandyGrip VG 20 w
- HandyGrip VG 21
- HandyGrip VG 20
- HandyQuick SQ51
- HandyQuick SQ81
- HandyQuick SQ 31



JUNCTION BOX

# 2K-12 AB-2,5<sup>2</sup>/w

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP55 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No

## Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%