



JUNCTION BOX

2K-12 AB-2,5²



2K-12 AB-2,5²

Junction box

85 x 85 x 37 mm

Article number: 34541201

Junction box acc. DIN EN 60670 (VDE 0606), 12 entries, 2 floor entries, with self-sealing, soft inlet membranes, tools not required for opening the cable entry, seal range 2 - 14 mm, with external fixing positions

grey, with screw terminal 5-poles - 2.5 mm²



Technical data

Measures

Width:	85 mm
Length:	85 mm
Height:	37 mm

Material

Base:	polypropylene, membrane out of TPE
Cover:	Polypropylen, Copolymer

Other attributes

Color:	miscellaneous
Rated cross section:	2,5 mm ²
Tackable:	No
Rated insulation voltage AC:	400 V

Accessory

ZEL 2K-12

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

HandyQuick SQ51

HandyQuick SQ81

HandyQuick SQ 31



JUNCTION BOX

2K-12 AB-2,5²

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP55 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%