


FDV Dokumentasjon

<p>AF210B</p> 	<p>3-polet AC/DC kabelskotilkobling AF210B</p>			
	<p>Varetekst</p> <p>AF 210B-30-11RT 100-250V 50/60Hz/DC</p>	<p>EI.Nr.</p> <p>4115324</p>	<p>ABB Art.Nr.</p> <p>1SFL517062R7011</p>	<p>EAN/GTIN</p> <p>7320500260333</p>
<p>Forvaltning</p>				
<p>Drift</p>	<p>Renhold</p>	<p>Ikke krav til renhold</p>		
	<p>Energiforbruk</p>	<p>Pull-in at Max Rated Control Circuit Voltage 50Hz 470 volt-ampere Pull-in at Max Rated Control Circuit Voltage 60Hz 470 volt-ampere Holding at Max Rated Control Circuit Voltage 60Hz 10 volt-ampere Holding at Max Rated Control Circuit Voltage 50Hz 10 volt-ampere Holding at Max Rated Control Circuit Voltage DC 2 watt Pull-in at Max Rated Control Circuit Voltage DC 520 watt</p>		
	<p>Henvisninger</p>	<p>Katalog ID : 1SBC100192C02</p>		
<p>Vedlikehold</p>	<p>Rutiner</p>	<p>Ingen krav til periodisk vedlikehold</p>		
	<p>Levetid</p>			
	<p>Annet</p>			
<p>Generelt</p>	<p>Dimensjoner: HxBxD = 227x140x180,5 millimetre</p> <p>Kontakter for jernbane mm, brann og røyk-hemmende utførelse</p>			
<p>Produsent</p> 	<p>Navn</p> <p>ABB AS Low Voltage Products</p>	<p>Adresse</p> <p>Postboks 94 1375 Billingstad</p>	<p>Tlf</p> <p>24 16 54 00</p>	<p>E-Post</p> <p>automasjonsprodukter@no.abb.com</p>