



JUNCTION BOX

# WK 040-L



## WK 040-L

### Junction box

87 x 87 x 45 mm

Article number: 40490701

Junction box acc. DIN EN 60670 (VDE 0606),  $U_i=690V$ , Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M20, seal range 8 - 13.5 mm

grey, without terminal



## Technical data

### Measures

Width:	87 mm
Length:	87 mm
Height:	45 mm

### Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

### Other attributes

Entries:	6
Rated cross section:	4 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	690 V

## Accessory

KVR M20-GDB/MGM

VST M20-or

AST M20-or

DMS M20

AST M20

KVR M20-GDB

KVR M20

GMU PA M20

ADR M20

WST M20

WNI M20

VST M20

VSS PA M20

SNI M20

BST M20

KS M20

DMS M20/sw



JUNCTION BOX

**WK 040-L**

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	None
Color:	grey

RST M20

Abox 025/040 KLS-2,5<sup>2</sup>/4<sup>2</sup>

WST M20/sw

WNI M20/sw

KVR M20-MGM/sw

KVR M20-GDB/MGM/sw

MPS-KRI

KVR M20-MGM

KVR M20-GDB/MGM

VST M20-or

AST M20-or

DMS M20

AST M20

**Environmental attributes**

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%