



JUNCTION BOX

WK 060-L



WK 060-L

Junction box

100 x 100 x 50 mm

Article number: 40690601

Junction box acc. DIN EN 60670 (VDE 0606), $U_i=690V$, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M25, seal range 9 - 18.5 mm

grey, without terminal



Technical data

Measures

Width:	100 mm
Length:	100 mm
Height:	50 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	6
Rated cross section:	6 mm²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

KVR M25-MGM

VST M25-or

AST M25-or

DMS M25

AST M25

WK 060 KLS-6²

KVR M25

GMU PA M25

ADR M25

WST M25

WNI M25

VST M25

VSS PA M25

SNI M25

KS M25

RST M25

WST M25/sw



JUNCTION BOX

WK 060-L

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	None
Color:	grey

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

WNI M25/sw

DMS M25/sw

KVR M25-MGM/sw

MPS-KRI

KVR M25-MGM

VST M25-or

AST M25-or

DMS M25

AST M25

WK 060 KLS-6²

KVR M25

GMU PA M25

ADR M25