



JUNCTION BOX

WK 100-L



WK 100-L

Junction box

115 x 115 x 66 mm

Article number: 41090601

Junction box acc. DIN EN 60670 (VDE 0606), $U_i=690V$, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M32, seal range 13 - 23 mm, with sealing kit

grey, without terminal



Technical data

Measures

Width:	115 mm
Length:	115 mm
Height:	66 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	6
Rated cross section:	10 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

- KVR M32-MGM
- VST M32-or
- AST M32-or
- DMS M32
- AST M32
- WK 100 KLS-10²
- KVR M32
- GMU PA M32
- ADR M32
- WST M32
- VST M32
- VSS PA M32
- SNI M32
- KS M32
- KST M32
- WNI M32
- RST M32



JUNCTION BOX

WK 100-L

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	None
Color:	grey

DMS M32/sw
KVR M32-MGM/sw
DMS M32/4
MPS-KRI
KVR M32-MGM
VST M32-or
AST M32-or
DMS M32
AST M32
WK 100 KLS-10 ²
KVR M32
GMU PA M32
ADR M32

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%