



CABLE JUNCTION BOX

WKE 402 RK



WKE 402 RK


Cable junction box

CUSTOMIZABLE

200 x 200 x 110 mm
Article number: 86240201

Cable junction and connection box with IP66 certified acc. EN 60670, with intrinsic fire resistance E30 acc. DIN 4102 Part 12, with isolation integrity FE180 acc. IEC 60331-11 as well as functional life F400 acc. EN 12101, housing and terminal blocks made from halogen-free special duroplastic

Junction box 5-pole, termination capability for each pole 2 x 2.5 - 35 mm², Accessories supplied:, Wall plug set ø 6 mm, 2 cable glands M50, seal range 23 - 34 mm



Technical data

Measures

Width:	200 mm
Length:	200 mm
Height:	110 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	Polyurethane
Cover screw:	stainless steel V2A

Other attributes

Color:	orange
Entries:	2
Rated cross section:	35 mm ²

Accessory

WKE 200 ABL

KVS

WKE 200 ABL

KVS



CABLE JUNCTION BOX

WKE 402 RK

Tackable:	No
Rated insulation voltage AC:	450 V
Explosion safety:	none
Fire protection:	E 30
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP66 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	Yes
Equipment:	Terminal

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%