



EMPTY ENCLOSURE

RK 4/12-L



RK 4/12-L

Empty enclosure

CUSTOMIZABLE

130 x 130 x 75 mm

Article number: 61390601

Terminal block housing, Polystyrene, grey, similar to RAL 7035, incl. 4 attachment bushes M20, seal range 8 - 13.5 mm, IP54, 1 adapter M25, seal range 9 - 18.5 mm

without terminals, with NS 35

IP66
IP54

IK07



Technical data

Measures

Width:	130 mm
Length:	130 mm
Height:	75 mm

Material

Base:	Polystyrene, grey, similar to RAL 7035
Cover:	Polystyrene, grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Other attributes

Ingress protection:	IP66/IP54 - acc. EN60529 / DIN VDE 0470-1
---------------------	---

Accessory

TK ABL

ASS-kl

HBA

KS M20

KS M25

KS M32



EMPTY ENCLOSURE

RK 4/12-L

Impact resistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
--------------------	---

Protection class:	II - isolate protection acc. VDE 0106
-------------------	---

Heavy metals-free:	Yes
--------------------	-----

PVC-free:	Yes
-----------	-----

Silicone-free:	Yes
----------------	-----

Combustion behaviour to UL:	HB acc. UL94
-----------------------------	--------------

Combustion behaviour to VDE:	650°C acc. VDE 0471/ EN 60695
------------------------------	----------------------------------

Fitted for outdoor application:	No
---------------------------------	----

Knockouts:	Yes
------------	-----

sealable:	Yes
-----------	-----

Weatherproof:	No
---------------	----

Equipment:	Mounting rail NS35
------------	--------------------

Environmental attributes

Ambient temperature (min.):	-25 °C
-----------------------------	--------

Ambient temperature (max.):	40 °C
-----------------------------	-------

Ambient temperature (24 h):	35 °C
-----------------------------	-------

Max. rel. humidity at 25° C (short Therm):	95%
---	-----

Max. rel. humidity at 40° C:	50%
------------------------------	-----