



JUNCTION BOX

WK 160-16²



WK 160-16²

Junction box

165 x 165 x 76 mm

Article number: 41641201

Junction box acc. DIN EN 60670 (VDE 0606), U_i=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M40, seal range 17 - 30 mm, with sealing kit

grey, with screw terminal 5-poles - 16 mm², (5 x 10² / 3 x 16²)



Technical data

Measures

Width:	165 mm
Length:	165 mm
Height:	76 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	12
Rated cross section:	16 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

WK 160 KLS-16²

WK 160 KLS-16²



JUNCTION BOX

WK 160-16²

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%