



JUNCTION BOX

WK 250-L

WK 250-L

Junction box

256 x 171 x 106 mm

Article number: 42591601

Junction box acc. DIN EN 60670 (VDE 0606), $U_i=690V$, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M40, seal range 17 - 30 mm, with sealing kit

grey, without terminal



Technical data

Measures

Width:	256 mm
Length:	171 mm
Height:	106 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	16
Rated cross section:	25 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

KVR M40-MGM

VST M40-or

AST M40-or

AST M40

WK 250 KLS-25²

KVR M40

GMU PA M40

ADR M40

WST M40

VST M40

SNI M40

KS M40

KVR M40-MGM/sw

KVR M40-MGM

VST M40-or

AST M40-or

AST M40



JUNCTION BOX

WK 250-L

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	None
Color:	grey

WK 250 KLS-25²

KVR M40

GMU PA M40

ADR M40

WST M40

VST M40

SNI M40

KS M40

KVR M40-MGM/sw

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%