



JUNCTION BOX

Abox 060-L



Abox 060-L

Junction box

CUSTOMIZABLE

110 x 110 x 67 mm
Article number: 80690701

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, with IP54 attachment bushes, with blanking plug M25, seal range 9 - 18.5 mm

grey, without terminal



Technical data

Measures

Width:	110 mm
Length:	110 mm
Height:	67 mm

Material

Base:	Polystyrene
Cover:	Polystyrene

Other attributes

Entries:	9
Rated cross section:	6 mm²
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none
Fire protection:	none

Accessory

Abox 060 KLS-6²

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M25-MGM

KVR M20-GDB/MGM

VST M25-or

VST M20-or

AST M25-or

AST M20-or

DMS M25

DMS M20



JUNCTION BOX

Abox 060-L

sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equiptment:	None
Color:	grey

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

AST M25
AST M20
KVR M25
KVR M20-GDB
KVR M20
GMU PA M25
GMU PA M20
ADR M25
ADR M20
WST M25
WST M20
WNI M25
WNI M20