




* representative image
Download photo


Dimensional



Download photo

GW93327

HIGH PERFORMANCE MINIATURE CIRCUIT BREAKER
- MTHP 160 - 2P CHARACTERISTIC C 80A- 3
MODULES



Check same range products

TECHNICAL DATA

Description	Code	No. of poles	No. modules
HIGH PERFORMANCE MINIATURE CIRCUIT BREAKER	MTHP 160	2P	3
Rated current	Curve	Rated voltage	Standard
80 A	C	230-400 V	EN 60898, EN 60947-2
Rated frequency (Hz)	Breaking capacity EN 60898 230V (Icn)	Breaking capacity EN 60898 400V (Icn)	Breaking capacity EN 60898 (Ics)
50/60 Hz	10000 A	10000 A	0.75 x Icn
Breaking capacity EN 60947-2 230V (Icu)	Breaking capacity EN 60947-2 400V (Icu)	Breaking capacity EN 60947-2 (Ics)	Insulation voltage
20 kA	16 kA	50% Icu	500 V

Rated impulse withstand voltage

6 kV

Minimum operating voltage

12V ac/dc

Maximum operating voltage

440V AC / 220V DC

Electrical endurance

10000

Mechanical endurance

20.000

Section rigid cable<=1x70 - <=2x25 - <=2x25+1x10
mm²**Section flexible cable**<=1x50(2) - <=2x25 - <=3x16 mm²**Rated tightening torque**

3.5 / 3 (terminals)

Operating temperature

-25 +60 °C

Stocking temperature

-40 +70 °C

Electrocod

1411

PRODUCT DOWNLOADProduct Data Sheet User guide Disposal **RANGE DOWNLOAD**Technical characteristics - IT Technical characteristics - EN Technical characteristics - DE **MARKS QUALITY****RELATED PRODUCTS****RELATED****GW96012**SHUNT TRIP
RELEASE 110-125V
DC/110-415V AC - 1...
MODULE**RANGE****GW40104**DISTRIBUTION
BOARD WITH
PANELS WITH...
WINDOW AND
EXTRACTABLE
FRAME - PRE-
ARRANGED FOR
TERMINAL BLOCK -
(12X2) 24M IP65**RELATED****GW95408**ADD ON RESIDUAL
CURRENT CIRCUIT
BREAKER FOR MTHP..
CIRCUIT BREAKER -
2P 125A TYPE AC
INSTANTANEOUS
Idn=0,3A - 4
MODULES**RELATED****GW96001**AUXILIARY CONTACT
OF OPEN/CLOSED
POSITION - 0,5...
MODULES**RELATED****GW96006**AUXILIARY CONTACT
OF FAULT
INDICATOR SWITCH..
0,5 MODULES

Customized solutions for you

*PRODUCTS AND SOLUTIONS FOR YOUR NEEDS***Professional****Private****Industry**

or

[Sign up now](#)



PRODUCTS

[Domotics](#)
[Power](#)
[Building](#)
[Lighting](#)
[Browse online the catalog](#) [BIM](#)

SERVICES

[Download](#)
[Technical assistance](#)
[Partner Sales Network](#)
[Softwares](#)

[CHANGE COUNTRY >](#)

COMPANY

[Mission](#)
[Advertising](#)
[References](#)
[Press](#)
[Corporate Governance](#)

[CONTACTS](#) [INTRASTAT](#) [LEGAL](#) [PRIVACY POLICY](#) [CONDITIONS](#)

WORK WITH US

Sole Shareholder Company. Registered Office: Via A. Volta, 1 - 24069 CENATE SOTTO BG - Italia
Tax and VAT code and registered with the Bergamo Chamber of Commerce in Bergamo, under the
registration number: 00385040167
Share capital 60.000.000,00 EUR Fully paid up.

Copyright ©2020 Gewiss S.p.A. P.IVA
00385040167