



CATALOG



SERIES



PRODUCT

Power



90 RCD Modular circuit brea..



COMPACT RESIDUAL CURREN..

Print



m




GW94360

COMPACT RESIDUAL CURRENT CIRCUIT BREAKER
WITH OVERCURRENT PROTECTION - MDC 60 - 3P
CURVE C 32A TYPE A $I_{dn}=0,3A$ - 3 MODULES

* representative image

Download photo

Dimensional



Download photo

[Check same range products](#)

TECHNICAL DATA

Description	Code	No. of poles	No. modules
RCCB WITH OVERCURRENT PROTECTION	MDC 60	3P	3
Rated current	Rated residual operating current	Type	Curve
32 A	300 mA	A	C
Rated voltage (EN/IEC 61009-1, 61009-2-1)	Standard	Rated frequency (Hz)	Breaking capacity EN 61009-1 400V (Icn)
400/415 V	IEC/EN 61009-1, IEC/EN 61009-2-1	50/60 Hz	6000 A
Breaking capacity EN 61009-1 (Ics)	Breaking capacity EN 60947-2 400V (Icu)	Breaking capacity EN 60947-2 (Ics)	Insulation voltage
1 x Icn	6 kA	100% Icu	500 V

Level of immunity (8/20 μs)

250 A

Rated impulse withstand voltage

4 kV

Overvoltage category

III

Electrical endurance

10000

Mechanical endurance

20.000

Section rigid cable<=1x35 - <=2x16 - <=1x16+2x10
mm²**Section flexible cable**<=1x35 - <=2x16 - <=1x16+2x10
mm²**Double connection**

YES (only down stream)

Rated tightening torque

2 Nm

Operating temperature

-25 +40 °C

Stocking temperature


-40 +70 °C

Auxiliaries compatibility

Yes

Assembly position

Any

PRODUCT DOWNLOADProduct Data Sheet User guide **RANGE DOWNLOAD**Technical characteristics - IT Technical characteristics - EN Technical characteristics - DE **MARKS QUALITY****RELATED PRODUCTS****GW96016**UNDER VOLTAGE
RELEASE - 230V AC -
1 MODULE**GWD4104**RESIDUAL CURRENT
CIRCUIT BREAKER -
IDP - 4P 25A TYPE A...
INSTANTANEOUS
Idn=0,3A - 4
MODULES**GW96001**AUXILIARY CONTACT
OF OPEN/CLOSED
POSITION - 0,5...
MODULES**GW40886**FLUSH-MOUNTING
DISTRIBUTION
BOARD - WITH...
BLANK DOOR - 24
MODULES (12X2)
IP40**GW46232**BOARD IN METAL
WITH BLANK DOOR
FITTED WITH...
TEMPERED GLASS
WINDOW AND LOCK
310X425X160 - IP55 -
GREY RAL 7035**GW90070**COMPACT
MINIATURE CIRCUIT
BREAKER - MTC 45 -..
3P CHARACTERISTIC
C 32A - 2MODULES

Customized solutions for you

PRODUCTS AND SOLUTIONS FOR YOUR NEEDS

Professional

Private

Industry

or

[Sign up now](#)



PRODUCTS

[Domotics](#)
[Power](#)
[Building](#)
[Lighting](#)
[Browse online the catalog](#) [BIM](#)

SERVICES

[Download](#)
[Technical assistance](#)
[Partner Sales Network](#)
[Softwares](#)

[CHANGE COUNTRY >](#)

COMPANY

[Mission](#)
[Advertising](#)
[References](#)
[Press](#)
[Corporate Governance](#)

[CONTACTS](#) [INTRASTAT](#) [LEGAL](#) [PRIVACY POLICY](#) [CONDITIONS](#)

WORK WITH US

Sole Shareholder Company. Registered Office: Via A. Volta, 1 - 24069 CENATE SOTTO BG - Italia
Tax and VAT code and registered with the Bergamo Chamber of Commerce in Bergamo, under the
registration number: 00385040167
Share capital 60.000.000,00 EUR Fully paid up.

Copyright ©2020 Gewiss S.p.A. P.IVA
00385040167