



CATALOG



SERIES



PRODUCT

Power

90 RCD Modular circuit brea..

COMPACT RESIDUAL CURREN.

Save in your list

Print

m




GW94366

COMPACT RESIDUAL CURRENT CIRCUIT BREAKER
WITH OVERCURRENT PROTECTION - MDC 60 - 4P
CURVE C 10A TYPE A $I_{dn}=0,03A$ - 4 MODULES

* representative image

Download photo

Dimensional



Download photo

[Check same range products](#)

TECHNICAL DATA

Description	Code	No. of poles	No. modules
RCCB WITH OVERCURRENT PROTECTION	MDC 60	4P	4
Rated current	Rated residual operating current	Type	Curve
10 A	30 mA	A	C
Rated voltage (EN/IEC 61009-1, 61009-2-1)	Standard	Rated frequency (Hz)	Breaking capacity EN 61009-1 400V (Icn)
400/415 V	IEC/EN 61009-1, IEC/EN 61009-2-1	50/60 Hz	6000 A
Breaking capacity EN 61009-1 (Ics) 1 x Icn	Breaking capacity EN 60947-2 400V (Icu)	Breaking capacity EN 60947-2 (Ics)	Insulation voltage
	6 kA	100% Icu	500 V

Level of immunity (8/20 μs)	Rated impulse withstand voltage	Overvoltage category	Electrical endurance
250 A	4 kV	III	10000
Mechanical endurance	Section rigid cable	Section flexible cable	Double connection
20.000	<=1x35 - <=2x16 - <=1x16+2x10 mm²	<=1x35 - <=2x16 - <=1x16+2x10 mm²	YES (only down stream)
Rated tightening torque	Operating temperature	Stocking temperature	Auxiliaries compatibility
2 Nm	-25 +40 °C	-40 +70 °C	Yes
ReStart compatibility	Assembly position		
Yes	Any		

PRODUCT DOWNLOAD

Product Data Sheet 

User guide 

RANGE DOWNLOAD

Technical characteristics - IT 

Technical characteristics - EN 

Technical characteristics - DE 

MARKS QUALITY



RELATED PRODUCTS



GW96001

AUXILIARY CONTACT
OF OPEN/CLOSED
POSITION - 0,5...
MODULES



GW96016

UNDER VOLTAGE
RELEASE - 230V AC -
1 MODULE



GW40104

DISTRIBUTION
BOARD WITH
PANELS WITH...
WINDOW AND
EXTRACTABLE
FRAME - PRE-
ARRANGED FOR
TERMINAL BLOCK -
(12X2) 24M IP65



GW90086

COMPACT
MINIATURE CIRCUIT
BREAKER - MTC 45 -..
4P CHARACTERISTIC
C 10A - 2MODULES



GW90988

RESTART RM PRO -
TO BE COUPLED
WITH MDC - 4 POLE...
- 1P+N/2P/4P
I_{dn}=0,1/0,3 A 230 V -
3 MODULES EN
50022



GWD4102

RESIDUAL CURRENT
CIRCUIT BREAKER -
IDP - 4P 25A TYPE A...
INSTANTANEOUS
Idn=0,03A - 4
MODULES

Customized solutions for you

PRODUCTS AND SOLUTIONS FOR YOUR NEEDS

Professional

Private

Industry

or

[Sign up now](#)



PRODUCTS

Domotics
Power
Building
Lighting
[Browse online the catalog BIM](#)

SERVICES

[Download](#)
[Technical assistance](#)
[Partner Sales Network](#)
[Softwares](#)

[CHANGE COUNTRY >](#)

COMPANY

[Mission](#)
[Advertising](#)
[References](#)
[Press](#)
[Corporate Governance](#)

WORK WITH US

Sole Shareholder Company. Registered Office: Via A. Volta, 1 - 24069 CENATE SOTTO BG - Italia
Tax and VAT code and registered with the Bergamo Chamber of Commerce in Bergamo, under the
registration number: 00385040167
Share capital 60.000.000,00 EUR Fully paid up.

Copyright ©2020 Gewiss S.p.A. P.IVA
00385040167