

**Logistic Data**

Article No.	31119104
Code	NL-T8 36W/865/G13
Product EAN	4008597191046
Customs tariff no.	85393110
Box quantity (pcs.)	25
EAN Box	4008597401534
Gross weight of box in kg	5.54
Length of box in m	1.25
Width of box in m	0.15
Height of box in m	0.15
ETIM class	EC000108
ETIM class name	Fluorescent lamp
Product status	Active

**Electric Parameters**


Lamp nominal wattage	36 W
Rated wattage	36.0 W
Energy Consumption kWh/1000h	42,37
Mains voltage	230 V

**Light Application Parameters**

Luminous flux	3250 lm
Luminous flux	3250 lm
max. luminous flux at	25 °C
Luminous efficiency	90.28 lm/W
Radium light colour	daylight
Colour temperature	6500 K
Colour temperature	6500 K
Colour rendering index Ra	80-89
Mean luminance	1.2
Lumen maintenance at 2000h	0.96
Lumen maintenance at 4000h	0.94
Lumen maintenance at 6000h	0.93
Lumen maintenance at 8000h	0.91
Lumen maintenance at 12000h	0.91
Lumen maintenance at 16000h	0.90
Lumen maintenance at 20000h	0.89

**Service Life**

Average nominal lifespan	20000 h
Average nominal lifespan	20000 h
Average nominal lifespan	20000 h
Lamp survival factor at 2000h	0.99
Lamp survival factor at 4000h	0.99
Lamp survival factor at 6000h	0.99
Lamp survival factor at 8000h	0.99
Lamp survival factor at 12000h	0.99
Lamp survival factor at 16000h	0.90
Lamp survival factor at 20000h	0.50





**Specification**

Diameter max.	26 mm
Length max.	1200 mm
Length	1200 mm
Mercury content	2.5 mg
dimmable	ja
Lamp shape	Rod
Colour	Other


**Notes**

Fluorescent lamp T8 - 26mm diameter, light colour 840, high luminous efficiency, good colour rendering, long life, base G13. Controllable by Dim-ECG.


Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage. The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

**Notes****Base**

G13  
IEC/EN 60061-1  
sheet 7004-51-8

**Spectrum**

light colour 865 Spectralux® daylight (11)



daylight(D 65)

**Special features****General notes**

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

**All technical data without guarantee.**