

PRODUKT DATBLAD

DALI REP LI | Signalforsterkere for LMS



CBP_03.00 AREAS OF APPLICAT, ALL [CALC.]

- Device for luminaire installation

CBP_02.00 PRODUCT BENEFITS, ALL [CALC.]

- The ECGs connected to the repeater operate as a group
- Can be addressed via DALI
- Cascadable

CBP_01.00 PRODUCT FEATURES, ALL [CALC.]


- Expansion of DALI systems by 64 ECGs each time
- Extends the DALI line by 300 m
- Touch DIM control of 64 DALI ECGs
- Maximum power input: 4 W

TEKNISK DATA

Elektriske data

Nominell spenning	230.00 V
Nettfrekvensen	50/60 Hz
System wattage [AGGR]	4,00 W

Mål og vekt



Lengde	189,0 mm
Bredde	30,0 mm
Høyde	21,0 mm
Produktvekt	69,00 g
Avstand monteringshull, lengderetning	180,0 mm

Temperatures & operating conditions

Omgivelsestemperatur-område	0...+50 °C
-----------------------------	------------

Egenskaper

Dimbar	No
Dimmingsgrensesnitt	DALI
Antall styreutganger	1
Installasjons type	Luminaire integration

Sertifikater og standarder

Beskyttelses type	IP20
Beskyttelsesklasse	II

CBP_08.00 EQUIPMENT / ACCES, ALL [CALC.]

- Independent installation in connection with LMS CI BOX

LAST NED DATA

Fil	
	Brochures 333877_Non-system-specific components – brochure
	Declarations of conformity 334845_Declaration of conformity – DALI Repeater
	Operating instructions 336809_DALI REPEATER LI OPERATING INSTRUCTION (GB)
	CAD data 3-dim 321295_DIM MULTI 3 DALI REP LI DALI MULTI 3 DALI EASY III TOUCH DIM RC
	CAD data PDF 321293_DALI MULTI 3 DALI EASY III DIM MULTI 3 DALI REP LI

LOGISTIKK DATA

Product kode	Produkt beskrivelse	Forpakkings enhet (stk/enhet)	Dimensjoner (lengde x bredde x høyde)	Volum	Brutto vekt
4008321292599		NO: VS 25	232 mm x 225 mm x 196 mm	10.23 dm ³	2755.60 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ANSVARSRASKRIVELSE

Endres uten varsel. Sørg alltid for å bruke den nyeste versjonen.