

# PRODUCT DATASHEET

## SST Duo Click Dim PAR 16 50 36° 5 W/827 GU10

LED DUO CLICK DIM PAR16 | LED reflector lamps PAR16 with retrofit pin base



### AREAS OF APPLICATION

- Wherever dimming was originally not planned
- Residential interiors
- Hospitality
- Outdoor applications only in suitable luminaires

### PRODUCT BENEFITS

- Easy dimming with double click of wall switch
- Easy and cost-effective operation, no dimmer required
- Long lifetime of up to 15,000 h
- Low energy consumption
- Easy relamping thanks to compact design
- Instant 100 % light, no warm-up time
- Makes rooms multi-purpose with adjustable light atmosphere

### PRODUCT FEATURES

- Provides modes for 100 % and 30 % light output
- Controllable via standard wall switch
- Good quality of light; color rendering index  $R_a \geq 80$
- Mercury-free lamps



## TECHNICAL DATA


### Electrical data

|                     |             |
|---------------------|-------------|
| Rated wattage       | 5.00 W      |
| Nominal wattage     | 5.00 W      |
| Nominal voltage     | 220...240 V |
| Operating frequency | 50...60 Hz  |

### Photometrical data

|   |            |
|---|------------|
| Rated color temperature                 | 2700 K     |
| Color rendering index Ra                | ≥80        |
| Lumen main.fact.at end of nom.life time | 0.70       |
| Light color (designation)               | Warm White |
| Nominal luminous flux                   | 350 lm     |

### Dimensions & weight



|                |         |
|----------------|---------|
| Overall length | 54.0 mm |
|----------------|---------|

### Lifespan

|                            |         |
|----------------------------|---------|
| Nominal lamp life time     | 15000 h |
| Rated lamp life time       | 15000 h |
| Number of switching cycles | 100000  |

### Additional product data

|                             |  |
|-----------------------------|--|
| Base (standard designation) | GU10   |
| Mercury-free                | Yes  |
| Product remark              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

## Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

## Country specific categorizations

|                 |                                |
|-----------------|--------------------------------|
| ILCOS           | DRPAR-5/827-220-240-GU10-50/36 |
| Order reference | SSTPR16502XD 5W                |

## LOGISTICAL DATA

| Product code  | Product description                                | Packaging unit<br>(Pieces/Unit) | Dimensions (length x<br>width x height) | Volume               | Gross weight |
|---------------|--|---------------------------------|---|----------------------|--------------|
| 4058075037601 | SST Duo Click Dim<br>PAR 16 50 36° 5<br>W/827 GU10 | Shipping carton box<br>10       | 290 mm x 254 mm x<br>134 mm             | 9.87 dm <sup>3</sup> | 729.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.