

Up- /Downlight ALVA 2x50° 10W 4000K AN On/Off

Item number EL10830105

The high-quality ALVA up/downlights are particularly suitable for the atmospheric illumination of building façades and passageways. Their tapered light cast upwards and downwards and two integrated light halos create a fascinating light effect. Multiple variants with different beam angles ensure a high degree of design flexibility.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
-------------------	------------------

Mounting location	Wall
-------------------	------

Terminal	2,5 mm² / 1,5 mm²
----------	-------------------

HOUSING

Dimensions	Length 176 mm x Width 100 mm x Height/Depth 160 mm
------------	--

Housing material	powder-coated aluminium
------------------	-------------------------

Protection type	IP 65
-----------------	-------

Permissible ambient temperature	-25 °C...+40 °C
---------------------------------	-----------------

Impact resistance	IK09
-------------------	------

Colour	Black grey, similar to RAL 7016
--------	---------------------------------

HOUSING

Weight	1,750 g
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	I
------------------	---

LIGHT

Diffusor	transparent
Light emission	direkt/indirekt
Beam angle	50 °
Flicker factor	<10 %
Rated output	10 W
Luminous Flux (light)	1,050 lm
Luminous efficacy	105 lm/W
LED service life	L ₈₀ B ₁₀ = 50.000 h
Colour temperature	4000 K
Colour rendering index R _a	> 80
Colour tolerance	SDCM <3
Color Quality Scale	80

Energy efficiency class

A++ to A