

STELLA 600 33W 4000K PRISMATIC ON/OFF

Item number EQ10600227

With their low profile design, LED panel lights in the STELLA series are well-suited to flexible applications in offices, learning environments and healthcare facilities. As such, they fulfil all requirements of contemporary light installations in terms of their straightforward handling, light quality and energy efficiency.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation length 595 mm x Installation width 595 mm x
Terminal	1.5 mm²

HOUSING

Dimensions	Length 600 mm x Width 600 mm x Height/Depth 9 mm
System dimensions	600x600
Housing material	painted aluminium
Surface finish	frosted
Protection type	IP 20

HOUSING

Permissible ambient temperature	0 °C...+50 °C
Colour	white, similar to RAL 9003
Weight	3,500 g
Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s

ELECTRICAL VERSION

Protection class	II
------------------	----

LIGHT

Diffusor	micro-prismatic / opal
Light emission	direkt
Beam angle	116 °
Unified Glare Rating	≤ 19
Flicker factor	<3%
Rated output	33 W
Luminous Flux (light)	3,800 lm
Luminous efficacy	115 lm/W
LED service life	L ₈₀ B ₅₀ = 50.000 h
Colour temperature	4000 K

LIGHT

Colour rendering index R_a > 80

Colour tolerance SDCM <3

Color Quality Scale >80

Photobiological safety Risk group 0

Energy efficiency class A++ to A

ACCESSORIES



PNL STELLA 1200mm Pendulum set

Item number EQ10600159



PNL STELLA 1000mm Pendulum set

Item number EQ10600166



PNL STELLA 600 mounting frame SM WH SLIM

Item number EQ10600173



PNL 600 UMF FM WH

Item number EQ10113086



PNL drop protection

Item number EQ10121616

