

PD-C 360i/24 ELC

Item number EP10427619

The Compact presence and motion detectors have successfully built themselves a reputation among our range of sensors as traditional favourites and true all-rounders. Their robust design and high level of performance are just as impressive as their huge versatility in terms of applications: Whether ceiling or wall detector, whether 230 V, KNX or DALI, whether switching, dimming or HVAC, they ensure a perfect combination of convenience and energy efficiency at all times — and offer an innovative solution with touch-sensitive lens surfaces thanks to the touch detectors.

TECHNICAL DATA

GENERAL

Conformity CE , RoHS , WEEE

MOUNTING

Installation type Recessed mounting

Mounting location Ceiling

Installation dimension Installation depth 24 mm, Ø 60 mm

Terminal 2,5 mm² / 1,5 mm²

HOUSING

Dimensions Height/Depth 46 mm, Ø 108 mm

Housing material UV-stabilised polycarbonate

Protection type recessed-mounted IP 20,
IP 54 with surface-mounted box (order separately),
IP 20 as recessed ceiling-mounted version (order installation set separately)

HOUSING

Permissible ambient temperature -25 °C...+50 °C

Relative humidity 5 - 93 %, non-condensing

Colour white, similar to RAL 9010

Weight 255 g

ELECTRICAL VERSION

Protection class III

SENSORS

Power consumption 0.3 W

Detection angle 360°

Detection range diagonally 24 m

Recommended installation height 3 m

Max. mounting height 10 m

Light measurement mixed light

Level of brightness approx. 5 - 2,000 lux

Slave input No

Fully automatic yes

Semi-automatic yes

SENSORS

Impulse feature yes

Constant lighting control 1

CONTROL

Channel 1 ESYLUX light control

Interface Switching/Dimming

Contact Bus system

Switch-off delay time approx. 1 min.-240 min.

Orientation light 10 % to 50 % luminous efficiency

Switch-off delay time, orientation light approx. 1 min.-240 min.

Master/slave function 1

Constant lighting control 1

Manual override yes, via IR

ACCESSORIES



ESY-Pen

Item number EP10425356



Mobil-PDi/MDi-universal

Item number EP10433993



Surface-mounted box-C IP 20

Item number EP10425370



Surface-mounted box-C IP 20

Item number EP10425387



Surface-mounted box C IP 54

Item number EP10425905
