

AFL SUN LED 10W 5K white

Item number EL10810077

The robust LED floodlights in the OFL/AFL SUN series are suited to brightly illuminating traffic routes, squares and garages — or for illuminating façades, signs and billboards. The optional motion detector provides automatic and therefore energy-efficient, convenient operation, while clever details simplify installation.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
Mounting location	Wall
Terminal	2,5 mm² / 1,5 mm²

HOUSING

Dimensions	Length 210 mm x Width 133 mm x Height/Depth 75 mm
Housing material	Aluminium and UV-stabilised plastic
Protection type	IP 65
Permissible ambient temperature	-25 °C...+40 °C
Colour	white, similar to RAL 9016
Weight	692 g

ELECTRICAL VERSION

Protection class	I
------------------	---

Stand-by consumption	0.5 W
----------------------	-------

LIGHT

Diffusor	transparent
----------	-------------

Light emission	direkt
----------------	--------

Beam angle	95 °
------------	------

Flicker factor	<20 %
----------------	-------

Rated output	9 W
--------------	-----

Luminous Flux (light)	1,020 lm
-----------------------	----------

Luminous efficacy	113 lm/W
-------------------	----------

LED service life	L ₈₀ B ₅₀ = 50.000 h
------------------	--

Colour temperature	5000 K
--------------------	--------

Colour rendering index R _a	> 80
---------------------------------------	------

Energy efficiency class	A++ to A
-------------------------	----------

SENSORS

Detection angle	160°
-----------------	------

Detection range diagonally	12 m
----------------------------	------

SENSORS

Range adjustment	mechanically with included cut to size lens mask
Recommended installation height	2.5 m
Level of brightness	approx. 5-1000 lux
Number of parallel switchable detectors	10

ACCESSORIES



Wall Arm 700 WH
Item number EL10810527