

OL 100 LED 3K

Item number EL10710711

The LED wall lights in the OL/AOL series are a timeless classic thanks to their elegant appearance and can be stylishly placed in any environment and improve the look of façades or entrance areas. The durable, die-cast aluminium housing makes them highly reliable and the optional integrated motion detector ensures convenient, energy-efficient operation. Clever details simplify installation.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
-------------------	------------------

Mounting location	Wall
-------------------	------

Terminal	2,5 mm² / 1,5 mm²
----------	-------------------

HOUSING

Dimensions	Length 143 mm x Width 104 mm x Height/Depth 205 mm
------------	--

Housing material	Aluminium and UV-stabilised plastic
------------------	-------------------------------------

Protection type	IP 55
-----------------	-------

Permissible ambient temperature	-25 °C...+50 °C
---------------------------------	-----------------

Colour	Black, similar to RAL 9005
--------	----------------------------

Weight	526 g
--------	-------

HOUSING

Glow wire test in accordance with IEC 60695-2-10	650 °C - 30 s
--	---------------

ELECTRICAL VERSION

Protection class	II
------------------	----

LIGHT

Diffusor	opal
Light emission	direkt
Beam angle	90 °
Flicker factor	<10 %
Rated output	14 W
Luminous Flux (light)	750 lm
Luminous efficacy	53 lm/W
LED service life	L ₈₀ B ₁₀ = 50.000 h
Colour temperature	3000 K
Colour rendering index R _a	> 80
Energy efficiency class	A++ to A

