

SLX 24 LEDi Display 3h

Item number EN10077371

The SLX series emergency lights provide variable LED solutions for indicating escape routes. Whether a classic, robust design, a modern, discreet design or a slim body especially for wall mounting: Thanks to the modular design concept, there is the right design for almost every requirement for the shared basic housing. In addition to the single-battery variants, versions for systems with central battery operation are also available.

TECHNICAL DATA

GENERAL

| | |
|------------|------------------|
| Conformity | CE , RoHS , WEEE |
|------------|------------------|

MOUNTING

| | |
|------------------------|---|
| Installation type | Surface mounting |
| Mounting location | Ceiling / Wall |
| Installation dimension | Installation length 370 mm x Installation width 115 mm x Installation depth 66 mm |
| Terminal | 2,5 mm² / 1,5 mm² |

HOUSING

| | |
|---------------------------------|--|
| Dimensions | Length 328 mm x Width 108 mm x Height/Depth 195 mm |
| Housing material | UV-stabilised polycarbonate |
| Protection type | IP 20 |
| Permissible ambient temperature | 5 °C...+35 °C |
| Colour | white, similar to RAL 9016 |

HOUSING

Weight 527 g

ELECTRICAL VERSION

Protection class II

NOTBELEUCHTUNG

Viewing distance 24 m (DIN)

Symbol height 120 mm

Light duration 3 h

Light emission direkt

Battery status indicator by LED

ACCESSORIES



SLX – Battery 3,6 V / 800 mAh

Item number EN10077401



Symbol panel 24 single-sided right

Item number EN10079054



Symbol panel 24 single-sided left

Item number EN10079061



Symbol panel 24 single-sided downwards

Item number EN10079078



Symbol panel 24 double-sided downwards/downwards

Item number EN10079085

