

ELX 20 LEDi Flat 3h

Item number EN10077227

With the same basic housing, the ELX series LED emergency lights supplement the escape route signage in the SLX series with a reliable, energy-efficient escape route light. In addition to the large illumination area, they impress with their versatile installation options and easy installation. Designs for systems with single-battery or central battery operation are available.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
Mounting location	Ceiling / Wall
Installation dimension	Installation length 430 mm x Installation width 155 mm x Installation depth 66 mm
Terminal	2,5 mm² / 1,5 mm²

HOUSING

Dimensions	Length 388 mm x Width 148 mm x Height/Depth 46 mm
Housing material	UV-stabilised polycarbonate
Protection type	IP 54
Permissible ambient temperature	5 °C...+35 °C
Relative humidity	5 - 95 %, non-condensing

HOUSING

Colour	white, similar to RAL 9016
--------	----------------------------

Weight	842 g
--------	-------

ELECTRICAL VERSION

Protection class	II
------------------	----

NOTBELEUCHTUNG

Light duration	3 h
----------------	-----

Light emission	direkt
----------------	--------

Battery status indicator	by LED
--------------------------	--------

ACCESSORIES



ELX – Battery 3,6 V / 1800 mAh

Item number EN10077418




Wall mounting bracket 110

Item number EN10077289



Universal installation frame 430

Item number EN10077234



Basket guard 80

Item number EN10077265



Pendulum set conduit

Item number EN10078316
