

SLX 24 LEDi Display 8h

Item number EN10077388

The SLX series emergency lights provide variable LED solutions for indicating escape routes. Whether a classic, robust design, a modern, discreet design or a slim body especially for wall mounting: Thanks to the modular design concept, there is the right design for almost every requirement for the shared basic housing. In addition to the single-battery variants, versions for systems with central battery operation are also available.

TECHNICAL DATA

GENERAL

Conformity CE , RoHS , WEEE

MOUNTING

Installation type Surface mounting

Mounting location Ceiling / Wall

Installation dimension Installation length 370 mm x Installation width 115 mm x Installation depth 66 mm

Terminal 2,5 mm² / 1,5 mm²

HOUSING

Dimensions Length 328 mm x Width 108 mm x Height/Depth 195 mm

Housing material UV-stabilised polycarbonate

Protection type IP 20

Permissible ambient temperature 5 °C...+35 °C

Colour white, similar to RAL 9016

HOUSING

Weight 527 g

ELECTRICAL VERSION

Protection class II

NOTBELEUCHTUNG

Viewing distance 24 m (DIN)

Symbol height 120 mm

Light duration 8 h

Light emission direkt

Battery status indicator by LED

ACCESSORIES



SLX – Battery 3,6 V / 800 mAh

Item number EN10077401



Symbol panel 24 single-sided right

Item number EN10079054



Symbol panel 24 single-sided left

Item number EN10079061



Symbol panel 24 single-sided downwards

Item number EN10079078



Symbol panel 24 double-sided downwards/downwards

Item number EN10079085

