

# SLX 24 LEDi Flat 3h

Item number EN10077241

The SLX series emergency lights provide variable LED solutions for indicating escape routes. Whether a classic, robust design, a modern, discreet design or a slim body especially for wall mounting: Thanks to the modular design concept, there is the right design for almost every requirement for the shared basic housing. In addition to the single-battery variants, versions for systems with central battery operation are also available.

## TECHNICAL DATA

### GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

### MOUNTING

Installation type	Surface mounting
Mounting location	Wall
Installation dimension	Installation length 430 mm x Installation width 155 mm x Installation depth 66 mm
Terminal	2,5 mm² / 1,5 mm²

### HOUSING

Dimensions	Length 388 mm x Width 148 mm x Height/Depth 46 mm
Housing material	UV-stabilised polycarbonate
Protection type	IP 54
Permissible ambient temperature	5 °C...+35 °C
Colour	white, similar to RAL 9016

HOUSING

Weight 698 g

ELECTRICAL VERSION

Protection class II

NOTBELEUCHTUNG

Viewing distance 24 m (DIN)

Symbol height 120 mm

Light duration 3 h

Light emission direkt

Battery status indicator by LED

ACCESSORIES



SLX – Battery 3,6 V / 800 mAh

Item number EN10077401



SLX 24 Flat symbol set 1 (replacement)

Item number EN10077500




SLX 24 Flat symbol set 2

Item number EN10077517



## Universal installation frame 430

Item number EN10077234



## Basket guard 80

Item number EN10077265