

OFL SUN LED 10W 3K white

Item number EL10810008

The robust LED floodlights in the OFL/AFL SUN series are suited to brightly illuminating traffic routes, squares and garages — or for illuminating façades, signs and billboards. The optional motion detector provides automatic and therefore energy-efficient, convenient operation, while clever details simplify installation.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
Mounting location	Wall
Terminal	2,5 mm² / 1,5 mm²

HOUSING

Dimensions	Length 150 mm x Width 133 mm x Height/Depth 75 mm
Housing material	Aluminium and UV-stabilised plastic
Protection type	IP 65
Permissible ambient temperature	-25 °C...+50 °C
Colour	white, similar to RAL 9016
Weight	480 g

ELECTRICAL VERSION

Protection class	I
------------------	---

LIGHT

Diffusor	transparent
----------	-------------

Light emission	direkt
----------------	--------

Beam angle	95 °
------------	------

Flicker factor	<20 %
----------------	-------

Rated output	9 W
--------------	-----

Luminous Flux (light)	950 lm
-----------------------	--------

Luminous efficacy	105 lm/W
-------------------	----------

LED service life	L ₈₀ B ₅₀ = 50.000 h
------------------	--

Colour temperature	3000 K
--------------------	--------

Colour rendering index R _a	> 80
---------------------------------------	------

Energy efficiency class	A++ to A
-------------------------	----------

ACCESSORIES



Wall Arm 700 WH

Item number EL10810527

