

# OFL SUN LED 30W 3K white

Item number EL10810107

The robust LED floodlights in the OFL/AFL SUN series are suited to brightly illuminating traffic routes, squares and garages — or for illuminating façades, signs and billboards. The optional motion detector provides automatic and therefore energy-efficient, convenient operation, while clever details simplify installation.

## TECHNICAL DATA

### GENERAL

|            |                  |
|------------|------------------|
| Conformity | CE , RoHS , WEEE |
|------------|------------------|

### MOUNTING

|                   |                   |
|-------------------|-------------------|
| Installation type | Surface mounting  |
| Mounting location | Wall              |
| Terminal          | 2,5 mm² / 1,5 mm² |

### HOUSING

|                                 |                                                   |
|---------------------------------|---------------------------------------------------|
| Dimensions                      | Length 252 mm x Width 227 mm x Height/Depth 86 mm |
| Housing material                | Aluminium and UV-stabilised plastic               |
| Protection type                 | IP 65                                             |
| Permissible ambient temperature | -25 °C...+50 °C                                   |
| Colour                          | white, similar to RAL 9016                        |
| Weight                          | 1,680 g                                           |

ELECTRICAL VERSION

Protection class I

LIGHT

Diffusor transparent

Light emission direkt

Beam angle 110 °

Flicker factor <20 %

Rated output 28 W

Luminous Flux (light) 3,370 lm

Luminous efficacy 120 lm/W

LED service life L<sub>80</sub>B<sub>50</sub> = 50.000 h

Colour temperature 3000 K

Colour rendering index R<sub>a</sub> > 80

Energy efficiency class A++ to A

ACCESSORIES



Wall Arm 700 WH  
Item number EL10810527

