

ELH O LED SC SM

Item number EN10080036

The ELH series provides escape route lighting for single-battery operation with a lens construction that is specially designed for extensive areas — either for oval illumination of floors or circular illumination of large rooms. Its larger-than-average range reduces the number of lights required. The integrated DALI interface ensures high levels of control flexibility during operation and convenient maintenance.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Surface mounting
-------------------	------------------

Mounting location	Ceiling
-------------------	---------

Terminal	2,5 mm² / 1,5 mm²
----------	-------------------

HOUSING

Dimensions	Length 190 mm x Width 190 mm x Height/Depth 44 mm
------------	---

Housing material	powder-coated metal
------------------	---------------------

Protection type	IP 20
-----------------	-------

Permissible ambient temperature	5 °C...+35 °C
---------------------------------	---------------

Relative humidity	5 - 95 %, non-condensing
-------------------	--------------------------

Colour	white, similar to RAL 9016
--------	----------------------------

HOUSING

Weight	1,170 g
--------	---------

ELECTRICAL VERSION

Protection class	I
------------------	---

NOTBELEUCHTUNG

Light duration	3 h
----------------	-----

Light emission	direkt
----------------	--------

Battery status indicator	by LED
--------------------------	--------