

BOLLARD ALVA 360° 940 / 170 16W 4000K ANTH. MILKY DALI

Item number EL10820267

The bollard lights in the ALVA series feature a high-quality design and are ideal for the intelligent lighting of paths, forecourts and driveways or green spaces. Their durability and die-cast aluminium housing ensure they meet all requirements for installation in public areas. The optional integrated motion detector provides energy-efficient, convenient operation.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Free standing
-------------------	---------------

Mounting location	Floor
-------------------	-------

Terminal	2,5 mm² / 1,5 mm²
----------	-------------------

HOUSING

Dimensions	Height/Depth 940 mm, Ø 170 mm
------------	-------------------------------

Housing material	powder-coated aluminium
------------------	-------------------------

Protection type	IP 65 (lamp head) IP 54 (connection box)
-----------------	--

Permissible ambient temperature	-25 °C...+40 °C
---------------------------------	-----------------

Impact resistance	IK09
-------------------	------

Colour	Black grey, similar to RAL 7016
--------	---------------------------------

HOUSING

Weight7,910 g

ELECTRICAL VERSION

Protection classI

LIGHT

Diffusoropal

Light emissiondirekt

Beam angle283 °

Flicker factor<10 %

Rated output16 W

Luminous Flux (light)980 lm

Luminous efficacy61 lm/W

LED service lifeL₈₀B₁₀ = 50.000 h

Colour temperature4000 K

Colour rendering index R_a> 80

Colour toleranceSDCM <3

Color Quality Scale80

Energy efficiency classA++ to A



ALVA ground anchor operating instructions

Item number **EL10820083**