

# Pendulum light PRANA+ 60 W TW CR CRYSTAL DALI

Item number EV10125027

The PRANA+ Pendulum Light meets the highest standards for representative design and light quality. The puristic design of the high-quality aluminium body contributes to the creation of a successful lighting atmosphere just as much as the aesthetic connection cable, which elegantly replaces the suspension. Clever options provide greater convenience: Direct and indirect light with individually controllable brightness and a variable tunable white.

## TECHNICAL DATA

### GENERAL

---

Conformity CE , RoHS , WEEE

### MOUNTING

---

Installation type Pendant

---

Mounting location Ceiling

---

Terminal 2,5 mm<sup>2</sup> / 1,5 mm<sup>2</sup>

### HOUSING

---

Dimensions Length 1200 mm x Width 335 mm x Height/Depth 28 mm

---

Housing material Aluminium

---

Protection type IP 20

---

Permissible ambient temperature 0 °C...+40 °C

---

Colour Chrome

---

Weight 9,000 g

## HOUSING

---

Glow wire test in accordance with IEC 60695-2-10

650 °C - 30 s

## ELECTRICAL VERSION

---

Protection class

II

## LIGHT

---

Diffusor

micro-prismatic / transparent

Light emission

direkt/indirekt

Beam angle

98 °

Unified Glare Rating

≤ 16

Flicker factor

0 %

Rated output

60 W

Luminous Flux (light)

6,760 lm

Luminous efficacy

112 lm/W

LED service life

L<sub>80</sub>B<sub>10</sub> = 50.000 h

Colour temperature

2700 K - 6500 K (Tunable White)

Colour rendering index R<sub>a</sub>

> 85

Colour tolerance

SDCM <3

Color Quality Scale

CQS > 85

## LIGHT

---

Photobiological safety

Risk group 0

---

Energy efficiency class

A++ to A