

# PD-C 360i/24 DRY

Item number EP10425707

The Compact presence and motion detectors have successfully built themselves a reputation among our range of sensors as traditional favourites and true all-rounders. Their robust design and high level of performance are just as impressive as their huge versatility in terms of applications: Whether ceiling or wall detector, whether 230 V, KNX or DALI, whether switching, dimming or HVAC, they ensure a perfect combination of convenience and energy efficiency at all times — and offer an innovative solution with touch-sensitive lens surfaces thanks to the touch detectors.

## TECHNICAL DATA

### GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

### MOUNTING

Installation type	Recessed mounting
-------------------	-------------------

Mounting location	Ceiling
-------------------	---------

Installation dimension	Installation depth 24 mm, Ø 60 mm
------------------------	-----------------------------------

Terminal	2,5 mm² / 1,5 mm²
----------	-------------------

### HOUSING

Dimensions	Height/Depth 46 mm, Ø 108 mm
------------	------------------------------

Housing material	UV-stabilised polycarbonate
------------------	-----------------------------

Protection type	recessed-mounted IP 20, IP 20/IP 54 with surface-mounted box (order separately), IP 20 as recessed ceiling-mounted version (order installation set separately)
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

**HOUSING**

Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010
Weight	251 g

**ELECTRICAL VERSION**

Protection class	II
------------------	----

**SENSORS**

Power consumption	0.3 W
Detection angle	360°
Detection range diagonally	24 m
Recommended installation height	3 m
Max. mounting height	10 m
Light measurement	mixed light
Level of brightness	approx. 5 - 2,000 lux
Slave input	yes
Max. number of slave detectors	10
Fully automatic	yes

## SENSORS

Semi-automatic	yes
----------------	-----

Impulse feature	yes
-----------------	-----

## CONTROL

### Channel 1

### Lighting

Interface	Switching
-----------	-----------

Contact	1 + 2, break contact/floating
---------	-------------------------------

Switching capacity channel 1	floating/NC 230 V AC/5 A, 24 V DC/5 A
------------------------------	---------------------------------------

In-rush current	Capacitive load/electronic ballasts max. in-rush current 30 A/20 ms
-----------------	---------------------------------------------------------------------

Switch-off delay time	impulse/approx. 1 minute – 30 minutes
-----------------------	---------------------------------------

Master/slave function	1
-----------------------	---

Manual override	yes
-----------------	-----

## ACCESSORIES



### PD-C 360/8 Slave

Item number EP10055379



### PD-C 360/24 Slave

Item number EP10055386



## PD-C 360i/32 Slave

Item number EP10427770

---



## ESY-Pen

Item number EP10425356

---



## Mobil-PDi/MDi

Item number EM10425509

---