

PD 360/8 Slave

Item number EM10425028

The tried-and-tested technology in the Standard series is suitable for many different applications in buildings. Multiple variants of the presence and motion detector enable flexible application thanks to the different fields of detection, installation types and further details.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 15 mm, Ø 60 mm
Terminal	2,5 mm² / 1,5 mm²

HOUSING

Dimensions	Height/Depth 48 mm, Ø 140 mm
Housing material	UV-stabilised polycarbonate
Protection type	recessed-mounted IP 20, IP 54 with surface-mounted box (order separately)
Permissible ambient temperature	0 °C...+50 °C
Relative humidity	5 - 95 %, non-condensing

HOUSING

Colour	white, similar to RAL 9010
Weight	223 g

ELECTRICAL VERSION

Protection class	II
------------------	----

SENSORS

Power consumption	0.4 W
Detection angle	360°
Detection range diagonally	8 m
Recommended installation height	3 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	nicht relevant
Slave input	No
Fully automatic	yes
Semi-automatic	No
Impulse feature	yes

## CONTROL

---

### Channel 1

### Presence

---

Interface

nicht relevant

---

Contact

Bus system

---

Switch-off delay time

nicht relevant

---

Master/slave function

1

---

Manual override

No

## ACCESSORIES

---




### ESY-Pen

Item number EP10425356



### Surface-mounted box IP 54

Item number EM10425400



### Cover set 360/8

Item number EM10425455



### Basket guard 165/70

Item number EM10425615



## Basket guard 180/90

Item number EM10425608

---