

MD/PD 180 Slave

Item number EM10410024

The tried-and-tested technology in the Standard series is suitable for many different applications in buildings. Multiple variants of the presence and motion detector enable flexible application thanks to the different fields of detection, installation types and further details.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Recessed mounting
Mounting location	Wall
Installation dimension	Installation length 61 mm x Installation width 61 mm x Installation depth 34 mm, Ø 61 mm
Terminal	2,5 mm² / 1,5 mm²

HOUSING

Dimensions	Length 70 mm x Width 70 mm x Height/Depth 29 mm
Housing material	UV-stabilised polycarbonate
Protection type	IP 20, IP 44 depending on cover (order separately)
Permissible ambient temperature	0 °C...+50 °C
Relative humidity	5 - 95 %, non-condensing

HOUSING

Colour	Opal matt
Weight	72 g

ELECTRICAL VERSION

Protection class	II
------------------	----

SENSORS

Power consumption	0.4 W
Detection angle	180° horizontal, 60° vertical
Detection range diagonally	16 m
Recommended installation height	1.1 m
Max. mounting height	2.2 m
Light measurement	mixed light
Level of brightness	nicht relevant
Slave input	No
Fully automatic	yes
Semi-automatic	No
Impulse feature	yes

CONTROL

Channel 1

Presence

Interface

nicht relevant

Contact

Bus system

Switch-off delay time

nicht relevant

Master/slave function

1

Manual override

No

ACCESSORIES



MD 180i/R

Item number EM10055010



PD 180i/R

Item number EM10410017



Cover IP 20

Item number EM10055102



Cover IP 20

Item number EM10055119



Cover IP 20

Item number EM10055126
