### MD-C 360i/12 mini

Item number EP10426018

When it is really important not to mar the aesthetic design of a room with technical elements, the mini presence and motion detectors are the perfect solution. Their tiny housings and extremely low installation heights mean that they retreat unobtrusively into the background, while nevertheless keeping a close eye on everything thanks to their high-quality sensor technology. They are available for all common operating technologies and consistently impress clients thanks to the particular ease of installation.

#### TECHNICAL DATA

GENERAL	
Conformity	CE , RoHS , WEEE
MOUNTING	
Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 45 mm, Ø 25 mm
Terminal	1.5 mm <sup>2</sup>
HOUSING	
Dimensions	Height/Depth 25 mm, Ø 58 mm
Housing material	UV-stabilised PE , UV-stabilised polycarbonate
Protection type	IP 55
Permissible ambient temperature	-25 °C+50 °C
Relative humidity	5 - 93 %, non-condensing

# **HOUSING** Colour Opal matt 205 g Weight **ELECTRICAL VERSION** Protection class Ш **SENSORS** Power consumption 0.2 W Detection angle 360° Detection range diagonally 12 m Recommended installation height 3 m Max. mounting height 5 m Light measurement mixed light Level of brightness approx. 5 - 2,000 lux Slave input No Number of parallel switchable detectors 10 Fully automatic yes Semi-automatic yes

yes

Impulse feature

### **CONTROL**

Channel 1	Lighting
Interface	Switching
Contact	make contact/non-floating
Switching capacity channel 1	230 V AC 50 Hz, 16 A relay, 2300 W/10 A (cos phi = 1), 1150 VA/5 A (cos phi = 0.5)
In-rush current	800 A / 200 μs
Switch-off delay time	impulse/approx. 1 minute – 15 minutes
Manual override	yes

## **ACCESSORIES**



### ESY-Pen

Item number EP10425356



### Mobil-PDi/MDi

Item number EM10425509



### Mobil-PDi/MDi-universal

Item number EP10433993



## SRM-230V relay module



Item number EP10426346

© 2018 ESYLUX GmbH