

PROTECTOR K 9 V lithium

Item number ER10018930

The Protector series provides comprehensive protection against typical hazards in buildings. Different detector variants allow monitoring of individual rooms – or networked monitoring of multiple rooms using the hazard warning control panel.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
Automatic testing	approx. every 45 seconds with fault display
Electronic smoke chamber test	at the push of a button
Networkability	up to 30 detectors by wire
Signal volume	approx. 85 dB/3 m

MOUNTING

Installation type	Surface mounting
Mounting location	Ceiling
Terminal	1.5 mm²

HOUSING

Dimensions	Height/Depth 48 mm, Ø 106 mm
Protection type	IP 20
Permissible ambient temperature	0 °C...+55 °C

HOUSING

Relative humidity

5 - 93 %, non-condensing

Colour

white, similar to RAL 9010

Weight

142 g

ELECTRICAL VERSION

Protection class

III

ACCESSORIES



PROTECTOR K surface-mounted box H20mm

Item number **ER10018992**



PROTECTOR K surface-mounted box H27mm

Item number **ER10018985**



Basket guard 180/90

Item number **EM10425608**



Basket guard 165/70

Item number **EM10425615**



PROTECTOR K switching relay

Item number **ER10018923**

