

PD-CE 360/8 Slave

Item number EP10510748

The presence and motion detectors in the CE series intelligently switch the lighting and impress with their clever design. The concept enables installation flush with the ceiling and guarantees a correspondingly subtle appearance that, for the most part, only leaves the lens visible. Installation is quick and easy — even express.

TECHNICAL DATA

GENERAL

Conformity	CE , RoHS , WEEE
------------	------------------

MOUNTING

Installation type	Recessed mounting
Mounting location	Ceiling
Installation dimension	Installation depth 67 mm, Ø 68 mm
Terminal	1.5 mm²

HOUSING

Dimensions	Height/Depth 24 mm, Ø 82 mm
Housing material	UV-stabilised polycarbonate , UV-stabilised PE
Protection type	IP 40
Permissible ambient temperature	-25 °C...+50 °C
Relative humidity	5 - 93 %, non-condensing

HOUSING

Colour	Opal matt
--------	-----------

Weight	159 g
--------	-------

ELECTRICAL VERSION

Protection class	II
------------------	----

SENSORS

Power consumption	0.3 W
-------------------	-------

Detection angle	360°
-----------------	------

Detection range diagonally	8 m
----------------------------	-----

Recommended installation height	3 m
---------------------------------	-----

Max. mounting height	5 m
----------------------	-----

Light measurement	none
-------------------	------

Level of brightness	nicht relevant
---------------------	----------------

Slave input	yes
-------------	-----

Fully automatic	No
-----------------	----

Semi-automatic	No
----------------	----

Impulse feature	yes
-----------------	-----

CONTROL

Channel 1

Lighting

Interface

nicht relevant

Contact

Bus system

Switch-off delay time

nicht relevant

Master/slave function

1

Manual override

No

ACCESSORIES



PD-CE 360i/8

Item number EP10510700



PD-CE 360i/8 GST

Item number EP10510717



PD-CE 360i/8 WAGO

Item number EP10510786



PD-CE 360i/24

Item number EP10510724



PD-CE 360i/24 GST

Item number EP10510731