

OFR 350 LED 5K

Item number EL10710308

Thanks to rear projection technology, OFR/AFR LED floodlights generate a powerful yet glare-free light that illuminates paths, squares and façades. What's more, they are optimally protected thanks to the aluminium housing and are particularly flexible thanks to the horizontally or vertically adjustable lamp head. The optional integrated motion detector ensures automatic energy efficiency.

TECHNICAL DATA

GENERAL

Conformity CE , RoHS , WEEE

MOUNTING

Installation type Surface mounting

Mounting location Wall

Terminal 2,5 mm² / 1,5 mm²

HOUSING

Dimensions Length 176 mm x Width 137 mm x Height/Depth 198 mm

Housing material Aluminium and UV-stabilised plastic

Protection type IP 55

Permissible ambient temperature -25 °C...+50 °C

Colour white, similar to RAL 9016

Weight 934 g

ELECTRICAL VERSION

Protection class II

LIGHT

Diffusor opal

Light emission direkt

Beam angle 120 °

Flicker factor <10 %

Rated output 26 W

Luminous Flux (light) 1,670 lm

Luminous efficacy 64 lm/W

LED service life $L_{80}B_{10} = 50.000$ h

Colour temperature 5000 K

Colour rendering index R_a > 70

Energy efficiency class A++ to A