Article number: 1039550

theMova S360 KNX AP WH Article number: 1039550

Description





- KNX Passive infrared motion detector for ceiling mounting
- Circular detection area 360°, up to Ø 9 m (64 m²)
- Mixed light measurement suitable for fl uorescent (FL/PL/ESL), halogen/ incandescent lamps and LEDs
- One lighting channels with one light measurement
- Switching operation
- Fully or semi-automatic
- Brightness switching value can be set in lux via parameters, the object or via remote control
- Teach-in of the brightness switching value
- Reduction of time delay when present briefly (short-term presence)
- Manual override by telegram or remote control
- One separate channel (presence) for controlling other devices such as HVAC systems with switch-on delay and time delay
- Master/Slave parallel switching for gap-free coverage of large areas
- Master/Master parallel switching for several lighting groups with separate light measurement, but joint presence detection
- Separate blocking objects for light and presence channel
- Detection and sending of current brightness
- Adjustable detection sensitivity
- Test mode for checking function and detection area
- Management remote control SendoPro 868-A (option)
- Installation remote control theSenda P (option)


Technical data

Operating voltage KNX	Bus voltage, ~9 mA	
Recommended installation height	2 – 3,5 m	
Setting range brightness	30 – 3000 lx	
Detection angle	360°	
Type of connection	KNX bus terminal	
Installation type	Ceiling installation	
Light switch-off delay	30 s - 60 min	
Lamps	Incandescent/halogen lamps, fluorescent lamps, Energy saving lamps, LEDs	
Light measurement	Mixed light measurement	
Presence switch-off delay	10 s - 120 min	
Switch-on delay presence	10 s – 30 min / inactive	
Ambient temperature	-15 °C +50 °C	
Type of protection	IP 20 (IP 54 when fitted)	

Detection range


Mounting height (A)	Head on to (r)	Diagonally (t)
2 m	5 m² 2,5 m	38 m² 7 m
2,5 m	7 m² 3 m	38 m² 7 m
3 m	13 m² 4 m	50 m² 8 m
3,5 m	13 m² 4 m	50 m² 8 m
4 m	13 m² 4 m	64 m² 9 m






Article number: 1039550

Scale drawings





Accessories

SendoPro 868-A

■ Article number: 9070675 Details ► www.theben.de



theSenda P

■ Article number: 9070910 Details ► www.theben.de



theSenda S

■ Article number: 9070911 Details ► www.theben.de

