

Product data sheet

Item No. 92.207.3004.1

Cable assembly GST18I4KS-S 15E 30SW

geis® Connection cable male - free end; length: 3m; type GST18I4; 4-pole; 250/400 V / 16 A; colour of coding: black with black strain-relief; cable: H05VV-F 4G1,5, colour: black, fire class Eca



Item No.	92.207.3004.1
EAN	4015573569249
Order Unit	20 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated voltage 2	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	2, N, PE, 1
Color of housing inclusive strain relief	Black

Model

Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP20
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends
Cable type	H05VV-F



Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Male - free end
Type of cord set	Connection cable
Version cable end 1	GST18i4 plug
Version cable end 2	Free end

Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C
Fire class	Eca

Dimensions

Total length	3 m
--------------	-----

Technical drawing

Pol / Aderfarbe / pole / colour of core

L2	schwarz / black
N	blau / blue
⊕	grün-gelb / green-yellow
L1	braun / brown

.F / Farbe / colour

.1	schwarz / black	1 PE N 2	schwarz / black
.2	weiß / white	1 PE N 2	weiß / white
.3	grau / grey	1 PE N 2	schwarz / black

Teile-Nr. / part-no.

92.207.XX04.F	XX in dm-Schritten	92.207.1004.1 = 10dm/L = 1000mm	Typ / type
U2.207.XX04.F	XX in m-Schritten	U2.207.1204.1 = 12 m/L = 12000mm	GST18i4KS-S 15 10SW
			GST18i4KS-S 15 X10SW

Weitere Daten siehe Katalog / further data see catalog

Typ/type: GST18i4KS-S 15

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey

PRE-ASSEMBLED CABLE KONFEKT-LEITUNG
Stecker/male - freies Ende/free end 1,5mm
Schraubanschluß/screw connection 250V