

Product data sheet

Item No. 96.834.1000.3

Cable assembly RST25I3KSBS 40P 10BG0

RST 25i3 extension cable female - male, 3 pole, assembled with screw connection, application 250V/400V, 25A, cable type H05VV-F, length 1.0m, cross section 4.0mm², coding-color concrete grey



| | |
|------------|---------------|
| Item No. | 96.834.1000.3 |
| EAN | 4015573896123 |
| Order Unit | 30 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|--|---------------|
| Rated current | 25 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Mechanical coding | Code 3 |
| Continuity resistor | 3 mOhm |
| Lockable | Yes |
| Color of coding/ contact carrier | Concrete gray |
| Marking of poles | L, N, PE |
| Color of housing inclusive strain relief | Black |

Model

| | |
|---------------------------------|-----------------------|
| type of construction | Cable screw gland |
| Nominal cross section conductor | 4 mm² |
| Degree of protection (IP) | IP66/68 (3m;2h) /IP69 |
| Cable type | H05VV-F |
| Cable colour | Black |
| Cable diameter | 11.4 mm |

| | |
|---------------------|-----------------|
| Version of cable | Female - male |
| Type of cord set | Extension cable |
| Version cable end 1 | female |
| Version cable end 2 | male |
| Screened | No |

Material

| | |
|--|---------------|
| Surface finish | Silver-plated |
| Halogen free | No |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 1 m |
|--------------|-----|



