

HENSEL

DK-koblingsbokser

Kabelinnføring via elastiske membraner



DE 9325 | El nr. 1243402

1,5-2,5 mm², Cu 3~


- Med koblingsstykke
- 5-polet pr. pol 6 x 1,5 mm² sol, 4 x 2,5 mm² sol, 3 x 4 mm² sol
- 10 tetningsmembraner, lukkede ledningsinnføringer, tetningsområde Ø 6,5-16 mm
- For beskyttet installasjon

Merkespenning

U_i = 690 V a.c./d.c.

Tiltrekningsmoment, klemme

1,2 Nm



DE 9345

1,5-4 mm², Cu 3~


- Med koblingsstykke
- 5-polet pr. pol 6 x 1,5 mm² sol, 4 x 2,5 mm² sol, 3 x 4 mm² sol, 2 x 6 mm² sol
- 10 tetningsmembraner, lukkede ledningsinnføringer, tetningsområde Ø 6,5-18 mm
- For beskyttet installasjon

Merkespenning

U_i = 690 V a.c./d.c.


Tiltrekningsmoment, klemme

1,2 Nm




DE 9320 | El nr. 1243401

- Uten koblingsstykke
- 10 tetningsmembraner, lukkede ledningsinnføringer, tetningsområde Ø 6,5-16 mm
- For beskyttet installasjon



DE 9340

- Uten koblingsstykke
- 10 tetningsmembraner, lukkede ledningsinnføringer, tetningsområde Ø 6,5-18 mm
- For beskyttet installasjon



KHR 01

Strekkavlaster

for kabeldiameter 6,5 - 14 mm

- Sett med 10 x 6 kabelholderinger
- 30 stk. for kabeldiameter 6,5 - 10 mm
- 30 stk. for kabeldiameter 10 - 14 mm



KHR 02

Strekkavlaster

for kabeldiameter 10 - 16 mm

- Sett med 10 x 6 kabelholderinger
- 30 stk. for kabeldiameter 10 - 14 mm
- 30 stk. for kabeldiameter 13 - 16 mm