

Product data sheet

Item No. 96.233.7003.1

Cable assembly RST20I3K1B- 25P 70SW

RST 20i3/2 connection cable female - free end, 3 pole, assembled with shrinkage tube, application 250V, 20A, cable type H05VV-F, length 7.0m, cross section 2.5mm², coding-color black



Item No.	96.233.7003.1
EAN	4015573760400
Order Unit	5 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Mechanical coding	Code 0
Continuity resistor	3 mOhm
Lockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	Black

Model

type of construction	Shrinkage tube
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP66/68 (3m;2h)
Wire strip length	9 mm
sheath strip length	35 mm
Preparation of conductor ends	Ultrasonically compressed wire ends



Cable type	H05VV-F
Cable colour	Black
Cable diameter	10.2 mm
Version of cable	Female - free end
Type of cord set	Connection cable
Version cable end 1	female
Version cable end 2	Free end

Material

Surface finish	Silver-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	7 m
--------------	-----

Technical drawing

Technical drawing showing a cable assembly with a connector. Dimensions include a diameter of $\varnothing 2.5$ mm and a length of ca. 8.2 mm. The cable is labeled '2,5" max 20A'. A color coding table is provided:

.F	Farbe colour	Codierung
.0	lichtgrau light grey	N
.1	schwarz black	

Additional details include: 'Gesamtlänge / Total length', 'Weitere Daten siehe Katalog further data see catalog', and 'Typ/type: RST2013K1B- 25P .. GL = lichtgrau/light grey SW = schwarz/black'.

Teile - Nr. part - no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
96.233.XX03.F	XX in dm-Schritten	96.233.1003.1 = 10dm/L= 1000mm	RST2013K1B- 25P 10SW
U6.233.XX03.F	XX in m-Schritten	U6.233.1203.1 = 12 m/L=12000mm	RST2013K1B- 25P X12SW

Wieland logo and 'KONFEKT_LEITUNG' (pre-assembled cable) are also present.