

FTCBI Insulated Flat Braid in Coil, Tinned Copper – FTCBI15-25 (503610)



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material
- Tinned finish provides a theft-deterrent appearance



Part Number	FTCBI15-25
Article Number	503610
Material	Copper Polyvinylchloride
Finish	Tinned
Nominal Current	150 A
Cross Section	25 mm ²
Number of Wires	1,404
Wire Diameter	0.15 mm
Length	100 m
Thickness	3.5 mm
Width	25 mm
Unit Weight	0.29 kg
Insulation Thickness	1 mm
Insulation Voltage	450 V
Temperature	70 °C Max
Flammability Rating	UL [®] 94V-0
Certifications	EAC 0234251 (Russian Federation) RoHS
Standard Packaging Quantity	100 m
UPC	78285687473
EAN-13	3479775036106

Unit weight is per meter (3.28').

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.