
## Universal Busbar Support with Neutral Circuit, High Ampacity – UBS2-10TN-160 (561870)







- Universal fixing system
- Installs quickly and easily
- Extremely robust construction
- Screws are made from non-magnetic stainless steel
- Halogen free insulators





Part Number	UBS2-10TN-160
Article Number	561870
Material	Glass Fibre Reinforced Polyamide Steel
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Working Temperature	-40 to 130 °C
Complies With	IEC® 60439.1 IEC® 61439.1
Flammability Rating	UL® 94V-0
Typical Application Current Rating	5,700 A
Busbars per Phase	1 – 2
Busbar Width	160 mm
Busbar Thickness	10 mm
Width (W)	480 mm
A	110 mm
Unit Weight	3.4 kg
Certifications	Bureau Veritas 41941 BV CE EAC 8546901000 (Russian Federation) IEC 61439-1 Busbar Supports RoHS
Standard Packaging Quantity	1 pc
UPC	78285687791
EAN-13	3479775618708





IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC. WARNING Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty. © 2016 Pentair All rights reserved
Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.
All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

**ERIFLEX** 

**PENTAIR**