





Disconnectable PEN System – PEN-D75 (568800)



- Dedicated product allowing separation from PEN to PE+N
- Unique solution for TN-C/TN-S networks
- Safe disconnectable system
- Clear identification
- Prevents measurement errors
- Avoid reconnection errors
- Screen stickers included in 12 languages



Part Number	PEN-D75
Article Number	568800
Complies With	IEC® 60439.1 IEC® 61439.1
Max Current Rating, IEC	125 A
Thread Size (TS)	M6
Busbar Width	15 mm
Busbar Thickness	5 mm
Depth (D)	68.2 mm
Height (H)	120 mm
Width (W)	96 mm
A	100 mm
B	75 mm
Unit Weight	0.55 kg
Certifications	RoHS
Standard Packaging Quantity	1 pc
UPC	78285666570
EAN-13	3479775688008

IEC is a registered trademark of the International Electrotechnical Commission.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.