

## Product data sheet

Item No. 92.050.4253.1

Distributor GST18I5V 2A1T V 2 SW

T-connector GST18i5, 5/3 pole, 1 input and 1 output 5 pole, 1 output 3 pole, L2, 250/400 V, 20 A, colour of coding: black



|            |               |
|------------|---------------|
| Item No.   | 92.050.4253.1 |
| EAN        | 4015573655010 |
| Order Unit | 100 Piece(s)  |

## Certificates / Approvals



## Technical data

### General

|                                  |                |
|----------------------------------|----------------|
| Rated current                    | 20 A           |
| Rated voltage                    | 250 V          |
| Rated voltage 2                  | 400 V          |
| Rated impulse voltage            | 4 kV           |
| Pollution degree                 | 2              |
| Mechanical coding                | Code 1         |
| Lockable                         | Yes            |
| Color of coding/ contact carrier | Black          |
| Marking of poles                 | 3, N, PE, 2, 1 |

### Model

|                           |               |
|---------------------------|---------------|
| Number of inputs          | 1             |
| Number of outputs         | 2             |
| Type of fastening         | No            |
| Degree of protection (IP) | IP20          |
| Type of distributor       | T-Distributor |

## Material

|                                              |               |
|----------------------------------------------|---------------|
| Housing material                             | Polyamide     |
| Halogen free                                 | Yes           |
| Contact material                             | CuZn          |
| Insulation components continuous temperature | 100 °C        |
| Surface finish                               | Silver-plated |

## Dimensions

|        |         |
|--------|---------|
| Length | 44 mm   |
| Width  | 47.7 mm |
| Height | 43 mm   |

## Technical drawing

